

DESIGN OF SEGMENTED OUTER ROTOR PERMANENT  
MAGNET FLUX SWITCHING MOTOR IN TRANSVERSE SHAPE  
FOR HIGH TORQUE APPLICATIONS

ENWELUM MBADIWE IGNATIUS

A thesis submitted in  
fulfillment of the requirement for the award of the  
Doctor of Philosophy in Electrical Engineering

Faculty of Electrical and Electronic Engineering  
Universiti Tun Hussein Onn Malaysia

MARCH 2020

This thesis is dedicated to my family for her patience and prayers



## ACKNOWLEDGEMENT

My Ph.D research work started as something that would not come to an end one day. I am thankful to my Institution for approving my application and provision of fund for the programme. In this research, I must admit that the experience of travelling to an unknown faraway place, for the first time in life, is not easy. One may likely miss the right road many times, forcing him to wander around and about many times in order to find the right way. It happened in my journey.

In everything I experienced, I am very grateful to my supervisor, Associate Prof. Dr. Erwan Sulaiman for accepting me to be one of his students. He was always willing to tell me to be courageous and do it this way and that way. In all the ways, they led to success. His guidance and support during the entire study made it possible for me to write this thesis. I am continually amazed by his wealth of knowledge, his discipline, research and technical skills.


At the Research Centre for Applied Electromagnetics, I wish to express my sincere thanks to the following colleagues: Faisal Khan who never turned me down whenever I went to him with questions and Md Zarafi Ahmad for every advice he offered in the difficult research process. Every member at the research centre has been greatly acknowledged. They include, Siti, Laili, Naufaul, Hassan, Irfan, Firdaus, Fairos and Abdul Rashid Omar Mumin. There are other friends whose names I would not mention due to lack of space. They provided useful information during my research time period.

In a very special way, I express my sincere gratitude to my wonderful family for being patient during my absence. Lastly, I did not forget everyone I did not know, for sure, whatever they did was helpful to raise up hope.

## ABSTRACT

The use of an outer rotor electric motor for electric vehicle applications has gained a lot of attention since the motor has high torque density and power. Outer rotor motors have performance indices that should be taken into consideration because not every machine is effective. Recently, outer rotor hybrid excitation flux switching motor (OR-HEFSM) in salient rotor has become attractive for providing high torque and high power. It uses two flux sources and single tooth winding. Regrettably, salient rotor and complex stator of HEFSM with single tooth winding have inherited high iron loss and high winding loss. Furthermore, HEFSM uses a high volume of permanent magnet (PM), suffers demagnetisation and low permeability resulting in poor performance. In another development, outer rotor field excitation FSM (OR-FEFSM), using dovetail segmented rotor in concentrated winding, has been presented for low-cost and high power-density. The OR-FEFSM using concentrated winding is capable of providing high power-density and sinusoidal back-emf, reasonable torque ripple and high net peak-torque. However, the problem of ORFEFSM is the utilisation of high number of stator teeth, high number of rotor segments and high number of copper conductor. These high materials usage lead to high iron and copper losses that affect performance of motor. This thesis deals with a newly designed structure of the segmented outer rotor permanent magnet flux switching motor in transverse shape (SegOR-PMFSM) with minimal iron and copper losses, high permeability, high torque and power output. The JMAG-Designer version 14 is utilised as the 2D finite element analysis (2D-FEA). For the three-phase operation, a 24 stator-teeth with feasible poles like 8, 10, 14, 16, 22 and 26 was designed, analysed and the results were compared based on torque and power performances. The 24S/14P motor is selected for securing the initial highest torque of 240.5 Nm and achieved the target average torque/power of 470 Nm/45 kW after using parameter optimisation method (POM). This result was compared with OR-HEFSM having torque/power of 335 Nm/123 kW and OR-FEFSM having torque/power of 380 Nm/29 kW. Meanwhile, the torque achieved with SegOR-

PMFSM is 28.72 % and 19.14 % higher than OR-HEFSM and OR-FEFSM. Motor's torque density and power density, at maximum armature current density are calculated to be 76.66 kNm/m<sup>3</sup> and 7339.5 kW/m<sup>3</sup> respectively. Therefore, the torque of 24S/14P topology in a segmented transverse shape has produced higher average torque than using salient rotor pole and dovetail segmented rotor in the machine design. The results obtained affirm good agreement with high torque for light-weight electric vehicle applications. The favourable high torque and power output of the proposed SegOR-PMFSM present it as a viable core component for electric vehicle application. However, this research is limited to 2D simulation analysis without experimental evaluations due to none availability of the testing equipment and the motor's weakness is potential high induced emf.



## ABSTRAK

Penggunaan motor elektrik pemutar luar bagi aplikasi kenderaan elektrik telah mendapat banyak perhatian kerana motor seperti ini mempunyai kuasa dan ketumpatan tork yang tinggi. Motor pemutar luar mempunyai indeks prestasi yang perlu dipertimbangkan kerana tidak setiap mesin berkesan. Baru-baru ini, pengayun fluks pengujian pemutar luar (OR-HEFSM) di pemutar utama menjadi tarikan dalam penghasilan tork dan kuasa yang tinggi. Ia menggunakan dua sumber fluks dan penggulangan gigi tunggal. Malangnya, pemutar utama dan pemegun kompleks HEFSM dengan penggulangan gigi tunggal telah memiliki kehilangan besi dan penggulangan yang tinggi. Tambahan pula, HEFSM menggunakan jumlah magnet kekal (PM) yang tinggi, mengalami demagnetisasi dan kebolehtelapan yang rendah menyebabkan prestasi menjadi lemah. Dalam perkembangan lain, medan pengujian pemutar luar FSM (OR-FEFSM), dengan menggunakan pemutar teruas ekor merpati dalam penggulangan terpumpum, telah dibentangkan untuk kos yang rendah dan ketumpatan kuasa yang tinggi. OR-FEFSM menggunakan penggulangan terpumpum mampu menyediakan ketumpatan kuasa tinggi dan back-emf berbentuk sinus, riak tork yang munasabah dan tork puncak tinggi yang tinggi. Walau bagaimanapun, masalah OR-FEFSM adalah penggunaan jumlah gigi pemegun yang tinggi, semen pemutar yang tinggi dan bilangan konduktor tembaga yang tinggi. Penggunaan bahan yang tinggi ini membawa kepada kehilangan besi dan tembaga yang banyak yang mempengaruhi prestasi motor. Tesis ini berkaitan dengan struktur reka betuk yang baru bagi motor penukaran fluks magnet pemutar kekal dalam bentuk melintang (SegOR-PMFSM) dengan kehilangan besi dan tembaga yang minimum, kebolehtelapan yang tinggi, tork dan keluaran kuasa yang tinggi. JMAG –Designer versi 14 digunakan sebagai analisis unsur terhingga 2D (2D-FEA). Bagi operasi tiga fasa, 24 gigi stator dengan kutub yang layak seperti 8, 10, 14, 16, 22 dan 26 direka bentuk, dianalisis dan keputusannya dibandingkan dengan tork dan prestasi kuasa. Motor 24S/14P dipilih untuk menguasai tork tertinggi yang awal iaitu 240.5 Nm dan

mencapai sasaran purata tork/kuasa 470 Nm/45 kW selepas mennunakan kaedah pengotimuman parameter (POM). Hasil ini dibandingkan dengan OR-HEFSM yang mempunyai tork/kuasa 335 Nm/123 kW dan OR-FEFSM mempunyai tork/kuasa 380 Nm/29 kW. Sementara itu, tork yang dicapai dengan SegOR-PMFSM adalah 28.72 % dan 19.14 % lebih tinggi daripada OR-HEFSM dan OR-FEFSM. Ketumpatan tork dan kuasa motor, pada kepadatan arus maksimum yang dikira masing-masing adalah 76.66 kNm/m<sup>3</sup> dan 7339.5 kW/m<sup>3</sup>. Oleh itu, tork bagi topologi 24S/14P dalam bentuk melintang telah menghasilkan tork purata yang lebih tinggi daripada menggunakan kutub rotor pemutar dan pemutar teruas ekor merpati dalam reka bentuk mesin. Hasil yang diperolehi mengesahkan perjanjian yang baik dengan tork yang tinggi untuk aplikasi kenderraan elektrik ringan. Tork dan keluaran kuasa yang tinggi bagi SegOR-PMFSM yang dicadangkan itu sebagai komponen teras yang berdaya maju untuk aplikasi kenderaan elektrik. Walau bagaimanapun, kajian ini adalah terhad kepada analisis simulasi 2D tanpa penilaian eksperimen kerana tiada peralatan ujian dan kelemahan motor yang memiliki potensi emf yang tinggi.



## CONTENTS

	<b>TITLE</b>	<b>i</b>
	<b>DECLARATION</b>	<b>ii</b>
	<b>DEDICATION</b>	<b>iii</b>
	<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
	<b>ABSTRACT</b>	<b>v</b>
	<b>ABSTRAK</b>	<b>vii</b>
	<b>CONTENTS</b>	<b>ix</b>
	<b>LIST OF TABLES</b>	<b>xiii</b>
	<b>LIST OF FIGURES</b>	<b>xiv</b>
	<b>LIST OF SYMBOLS AND ABBREVIATIONS</b>	<b>xvii</b>
	<b>LIST OF APPENDICES</b>	<b>xxi</b>
<b>CHAPTER 1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Research background	1
	1.2 Problem statements	3
	1.3 Objectives of the research	4
	1.4 Scopes of work	5
	1.5 Research contributions	5
	1.6 Thesis organisation	6
<b>CHAPTER 2</b>	<b>REVIEW OF FLUX SWITCHING MOTORS</b>	<b>7</b>
	2.1 Introduction	7
	2.2 Electric vehicle motors	7
	2.3 Flux switching motor and operation principle	9
	2.3.1 Permanent magnet flux switching motor (PMFSM)	11
	2.3.2 Field excitation flux switching motor (FEFSM)	11



2.3.3 Hybrid excitation flux switching motor (HEFSM)	16
2.4 Performance comparison of PMFSM, HEFSM and FEFSM	19
2.5 Review of permanent magnet flux switching machine	20
2.5.1 Stator segmentation and reduction of PM usage in PMFSM	25
2.6 PMFSM in outer rotor configuration	27
2.7 PMFSM with segmented rotor	28
2.8 Segmented rotor pole and salient rotor pole in FSM design	29
2.9 Design parameter consideration for outer rotor motor	30
2.9.1 Torque requirement	30
2.9.2 Rating of the machine	31
2.9.3 Specific magnetic loading	31
2.9.4 Specific electric loading	32
2.9.5 Output equation of motor	32
2.10 Mathematical modelling of SegOR-PMFSM	33
2.11 Segmented rotor shapes	36
2.12 Review of optimisation methods	39
2.12.1 Parameter optimisation method	40
2.13 Summary	45
<b>CHAPTER 3 DESIGN METHODOLOGY</b>	<b>0</b>
3.1 Introduction	0
3.2 Choice of electric motor	0
3.2.1 Choice of the number of stator teeth	48
3.2.2 Classifications of stator core and armature winding in PMFSM	49
3.2.2 Introduction to JMAG Software tool	50
3.2.3 Design of segmented rotor shape	51
3.3 Initial design of the proposed SegOR-PMFSM	51
3.3.1 Operating principle of SegOR-PMFSM and armature coil test	57

3.3.2 Performance analysis of SegOR-PMFSM at various rotor segments	58
3.3.3 Torque and power against speed characteristics	59
3.3.4 Torque density and power density of the motor	60
3.3.5 Losses and efficiency of the motor	61
3.4 Parameter optimisation of SegOR-PMFSM	63
3.4.1 Rotor mechanical properties	64
3.5 Summary	64
<b>CHAPTER 4 CHARACTERISTICS INVESTIGATIONS AND PERFORMANCE OF THE PROPOSED SEGMENTED OUTER ROTOR (SEGOR) PMFSM</b>	<b>65</b>
4.1 Introduction	65
4.2 Analysis of 12S/14P OR-HEFSM in salient rotor on the basis of FEA	65
4.3 Analysis of 36S/21P OR-FEFSM in rotor segment on the basis of FEA	66
4.3.1 Performance comparison of different segmented rotor shapes	67
4.4 Analysis of SegOR-PMFSM with various numbers of rotor segments	67
4.4.1 Coil test analysis and operating principle of SegOR-PMFSM	68
4.5 Flux performance analysis of SegOR-PMFSM under no-load condition	72
4.5.1 Cogging torque of SegOR-PMFSM	73
4.5.2 Induced back-emf of SegOR-PMFSM at no-load condition	74
4.5.3 Performance analysis of SegOR-PMFSM under current density, $J_a$	76
4.5.4 Torque and power versus speed characteristics of 24S/10P and 24S/14P SegOR-PMFSMs	78
4.5.5 Motor losses in initial 24S/10P design	79
4.5.6 Motor losses in initial 24S/14P design	81
4.6 Parameter optimisation of 24S/14P SegOR-PMFSM	83

4.7	Performance analysis of optimised SegOR-PMFSM	90
4.7.1	Flux comparison of initial and optimised SegOR-PMFSM	91
4.7.2	Cogging torque and harmonic distortion of optimised SegOR-PMFSM	92
4.7.3	Induced back-emf comparison of initial and optimised designs	94
4.7.4	Torque performance of SegOR-PMFSM at armature current density	94
4.7.5	Torque and speed characteristics of 24S/14P SegOR-PMFSM	95
4.7.6	Parameter losses and efficiencies of SegOR-PMFSM	97
4.7.7	Rotor mechanical stress	99
4.7.8	Performance comparison of SegOR-PMFSM with other motors	100
4.8	Summary	102
<b>CHAPTER 5</b>	<b>CONCLUSIONS AND FUTURE WORKS</b>	<b>103</b>
5.1	Conclusions	103
5.2	Future works	104
	<b>REFERENCES</b>	<b>105</b>
	<b>APPENDICES A-C</b>	<b>119</b>
	<b>VITA</b>	<b>126</b>

## LIST OF TABLES

2.1	Performance comparison of PMFSM, FEFSM and HEFSM [86]	20
2.2	Comparison of of flux excitation sources of FSMs [87]	20
2.3	Performance comparison of segmented and salient rotors	30
2.4	Comparison between salient rotor and segmented rotor	37
2.5	PMFSMs performance and characteristics of previous works	42
2. 6	Performance comparison of different PMFSMs for various applications	43
3.1	Design specifications and parameters of SegOR-PMFSM	53
3.2	Materials used for the SegOR-PMFSM	55
4.1	Characteristics performances of the designed motors	76
4.2	Performance comparison of the motors output torque	77
4.3	Torque and power densities	83
4.4	Parameters of initial and optimised design structures	86
4.5	Performance comparison between initial and optimised designs	100
4.6	Performance comparison with other motors for high torque applications	101

## LIST OF FIGURES

1.1	Cross-sections of three-phase outer rotor motors (a) OR-FEFSM (segmented rotor) [40] (b) OR-HEFSM (salient rotor) [37] (c) OR-PMFSM (salient rotor) [35] (d) SegStator-ORPMSM (round rotor) [21]	3
2.1	Classifications of FSMs [50]	9
2.2	Single-phase 4S/2P flux switch alternator (inner rotor) [48]	10
2.3	Basic single phase 4S/2P configuration of FEFSM [59]	12
2.4	Single-phase FEFSM	13
2.5	Single-phase FEFSM	14
2.6	Three-phase 24S/10P FEFSM	15
2.7	Three-phase 12S/8P FEFSMs for critical applications [70]	16
2.8	Two examples of three-phase HEFSM	17
2.9	Three-phase 12S/10P HEFSM [82]	17
2.10	Idealised three-phase HEFSMs	18
2.11	Cross-sections of three-phase idealized 12S/10P HEFSM	19
2.12	Example of single-phase PMFSMs	21
2.13	Single-phase PMFSM with compact disc [94]	22
2.14	Earliest three-phase PMFSMs for high density speed [95] (a) 6S/14P PMFSM (Type A) (b) 12S/10P PMFSM (Type B)	23
2.15	Three-phase PMFSMs for various applications	24
2.16	Three-phase PMFSMs (reduced PM volume) (a) 12S/10P PMFSM (Conventional) (b) 6S/10P PMFSM (C-core) (c) 6S/10P PMFSM (E-core) (d) 2x12S/19P	

	PMFSM (multi stator tooth) (e) 6S/10P PMFSM (multi-PM) (f) 12S/34P PMFSM (new multi-PMs)	26
2.17	Three-phase 12S/22P PMFSMs	27
2.18	Operating principle of outer rotor PMFSM (salient rotor) [105] (a) First alignment (b) Second alignment	28
2.19	Three-phase PMFSM (a) 12S/8P PMFSM (Segmental rotor) [109] (b) 12S/5P PMFSM (Modular rotor) [110]	29
2.20	Flux lines and flux distribution between segmented rotor and salient rotor (a) Segmented rotor (b) Salient rotor	30
2.21	The definition of $d$ -axis and $q$ -axis	33
2.22	Geometries of rotor segment shapes [40] (a) Dovetail (b) Transverse (c) Groove	37
3.1	Flowchart for research implementation	47
3.2	Cross-sections of FSM types	49
3.3	Design classifications of PMFSM structure	50
3.4	Structural chart of the proposed novel SegOR-PMFSM	50
3.5	Workflow of motor design, coil arrangement test and investigation analysis	52
3.6	Design parameters of SegOR-PMFSM	54
3.7	Main dimensions of 24S/14P SegOR-PMFSM	55
3.8	Three-phase stator-rotor segment numbers of SegOR-PMFSM	56
3.9	Flowchart of coil test and zero rotor analysis	57
3.10	Typical torque and power versus speed characteristics of FSM	60
3.11	Volume of estimated coil end of SegOR-PMFSM	61
3.12	Defined free motor parts for parameter optimisation	63
4.1	Average torque versus armature current phase angle	66
4.2	Torque of the OR-FEFSM in rotor segment at peak condition	66
4.3	Performance comparison of rotor shape flux linkages	67
4.4	Flux lines and flux linkage in terms of U, V and W (a) 24S/8P (b) 24S/10P (c) 24S/14P	69

4.5	Rectilinear representation of operating principle of SegOR-PMFSM	71
4.6	Open circuit field distribution of SegOR-PMFSM	71
4.7	Comparison of U-phase flux linkage of SegOR-PMFSMs	72
4.8	Cogging torque profile of the motors	73
4.9	Magnitude of cogging torque of initial motors design	74
4.10	Waveforms of induced back-emf at 1,900 rev/min in one period	76
4.11	Torque versus armature current density	77
4.12	Torque and power versus speed characteristics	78
4.13	Iron loss in 24S/10P SegOR-PMFSM at each operating point	79
4.14	Copper loss in the winding due to current	80
4.15	Iron losses in rotor and stator, and copper loss at various points	80
4.16	Motor losses and efficiency for operating points shown in Figure 4.12	81
4.17	Iron loss in 24S/14P SegOR-PMFSM at each operating point	82
4.18	Copper loss in the winding due to current	82
4.19	Iron losses in rotor and stator, and copper loss at various points	82
4.20	Motor losses and efficiency for operating points shown in Figure 4.12	83
4.21	Flowchart for optimisation process	85
4.22	Torque versus inner segment rotor radius, $D$ ( $\theta, W, M1, M2, A1, A2$ constant)	86
4.23	Torque versus segment rotor span, $\theta$ ( $D, W, M1, M2, A1, A2$ constant)	87
4.24	Torque versus segment rotor width $W$ ( $D, \theta, M1, M2, A1, A2$ constant)	88
4.25	Torque versus PM width $M1, M2$ ( $D, \theta, W, A1, A2$ constant)	88

4.26	Average torque versus stator tooth width $A1, A2, (D, \theta, W, M1, M2 \text{ constant})$	89
4.27	Effects of optimised parameters on the average torque	90
4.28	Optimised design 24S/14P SegOR-PMFSM	90
4.29	Magnetic flux linkage comparison of initial and optimised designs	91
4.30	Magnetic flux lines comparison of initial and optimised designs	92
4.31	Cogging torque comparison of 24S/14P SegOR-PMFSM	93
4.32	Harmonics content of 24S/14P SegOR-PMFSM	93
4.33	Comparison of induced back-emf of initial and optimised designs	94
4.34	Torque performance at various armature current density $J_a$	95
4.35	Torque versus speed characteristics of SegOR-PMFSM	96
4.36	Power versus speed characteristics of SegOR-PMFSM	97
4.37	Plot of instantaneous torque comparison	97
4.38	Torque and power versus speed of optimised design at specific operating points	98
4.39	Iron loss and copper loss at various points	99
4.40	Efficiency and motor losses at operating points	99
4.41	Rotor segment stress analysis at 898 rev/min	100



## LIST OF SYMBOLS AND ABBREVIATIONS

$\psi_d$	- d-axis flux linkage
$\psi_q$	- q-axis flux linkage
$\psi_m$	- Magnitude of fundamental component
$\alpha$	- Filling factor of armature coil
$\phi_a$	- Aligned flux
$\theta_a$	- Rotor position between U1 and d-axis
$\phi_p$	- Flux per pole
$\theta_r$	- Electrical angular position of rotor
$\theta_s$	- Segment angle span
$\omega_r$	- Rotor rotational speed
$\eta$	- Efficiency
$\eta_a$	- Hysteresis coefficient
$\rho$	- Copper resistivity
$a.c$	- Armature conductor
$A1$	- Armature slot width
$A2$	- Armature slot length
$B_{ave}$	- Specific magnetic loading
$B_{max}$	- Maximum flux density
$C_o$	- Output coefficient
$D_{or}$	- Outer rotor diameter
$E_{ph}$	- Voltage output per phase
$f_e$	- Electrical frequency

$f_m$	- Mechanical rotational frequency
$I_a$	- Armature current
$I_d$	- d-axis current
$I_{ph}$	- Current per phase
$I_q$	- q-axis current
$I_1$	- Current carrying conductor
$I$	- Peak phase current
$J_a$	- Armature current density
$k_e$	- Eddy current constant
$kW$	- Kilowatt
$L_a$	- Stack-length
$L_o$	- Magnitude component of self-inductance
$L_{-end}$	- Estimate air-gap length
$N_a$	- Number of turns
$N_{a-slot}$	- Number of armature slot
$P_c$	- Copper loss
$P_d$	- Power developed
$P_e$	- Eddy current loss
$P_h$	- Hysteresis loss
$P_i$	- Iron loss
$P_{in}$	- Electrical power
$P_o$	- Power output
$P_{out}$	- Electrical power developed
$P_{loss}$	- Machine power loss
$R_c$	- Resistance of winding coil
$P_r$	- Rotor pole number
$M1$	- Length of permanent magnet
$M2$	- Width of permanent magnet
$rms$	- Root mean square
$rps$	- Revolution per second
$mmf$	- Magnetomotive force

$S_a$	- Armature slot area
$t$	- Time
$t_a$	- Thickness of material
$T_{em}$	- Electromagnetic torque
$T_d$	- Torque developed
$V_1$	- Volume of coil slot
$V_2$	- Volume of coil end
$W_a$	- Armature coil copper
<i>SegOR</i>	- Segmented outer rotor
<i>SegStator</i>	- Segmented stator
$D$	- Distance of inner rotor radius
$Dl$	- Length of rotor segment
<i>DFT</i>	- Discrete fourier transform
<i>POM</i>	- Parameter optimisation method
<i>DC</i>	- Direct current
<i>EM</i>	- Electric motor
<i>EV</i>	- Electric vehicle
<i>FEV</i>	- Full electric vehicle
<i>FEA</i>	- Finite element analysis
<i>FEFSM</i>	- Field excitation flux switching motor
<i>FSM</i>	- Flux switching motor
<i>HEFSM</i>	- Hybrid excitation flux switching motor
<i>ICE</i>	- Internal combustion engine
<i>IPMSM</i>	- Interior permanent magnet synchronous motor
<i>IM</i>	- Induction motor
<i>PM</i>	- Permanent magnet
<i>PMFSM</i>	- Permanent magnet flux switching motor
$Q$	- Output equation
<i>SegOR-PMFSM</i>	- Segmented outer rotor permanent magnet flux switching motor
<i>SRM</i>	- Switched reluctance motor
$W$	- Width of rotor segment
$V$	- Total volume of coil
$Z$	- Number of conductors per phase

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	LIST OF PUBLICATIONS AND AWARDS	119
B	PM CALCULATION	122
C	DATA SHEET	123



**PT TA UTHM**  
PERPUSTAKAAN TUNKU TUN AMINAH



## CHAPTER 1

### INTRODUCTION

#### 1.1 Research background

It is obvious that the use of electric motor (EM) is so much important in our world, economically and environmentally for innovative development. As a result, great advances have been made in improving the performance of electric motors in order to be suitable for applications such as automotive and aerospace. These improvements are in the aspect of torque, power, efficiency, speed range, reliability and controllability [1-3]. For automotive applications without gearing, the requirements include high torque, high efficiency, high precision, less heat loss, less weight, little use of start-up energy and less vibration. Therefore, high torque electric motors are used for automotive application such as light weight fully electric vehicle (FEV) [4-7]. Outer rotor motor application is one of the solutions for saving energy and sustaining greenhouse vehicles [8]. EM provides torque and speed for applications and has proven to be a core component in this development and transformation process [9-11]. Torque of EM determines its performance and category of applications therefore, research for high torque motors is crucially significant for sustainable applications. The latest research and development have made possible many in-wheel automotive applications to be equipped with high torque electric motors [12,13].

Permanent magnet synchronous motor (PMSM) is used for automotive applications due to its superior magnetic properties such as high torque density, high torque, high efficiency, wide speed range and maintenance free operation but it locates active materials on the rotor [14-17]. The drawbacks of PMSM include increased high PM volume, limited field weakening capability, reduced slot surface area and high heat loss [18-20]. Meanwhile, segmented stator outer rotor permanent magnet

synchronous motor (SegStator-ORPMSM) has been proposed for light weight in-wheel application [21]. SegStator-ORPMSM consists of a four-cell segmented stator core. It uses all-stator teeth armature winding with permanent magnet (PM) mounted on the rotor. SegStator-ORPMSM is capable of high flux density, high torque and efficiency, but it has high material usage with PMs mounted on the rotating rotor which obviously affect the performance at speedy operation. Obviously, many electric motors have been developed but performance indices have to be taken into consideration because not every motor design is effective [22-24].

In another development, flux switching motor (FSM) is an advanced form of synchronous motor (SM) built by combining the structures of switched reluctance machine and inductor alternator with no active material located on the rotor [25-27]. FSM has internal three types which are (1) Permanent Magnet FSM (PMFSM) using PM flux source, (2) Field Excitation FSM (FEFSM) using field coil source and (3) Hybrid Excitation FSM (HEFSM) using both PM and field coil excitation sources. [28-31]. Due to its construction and characteristics, FSM has the advantages of less material usage, light weight and speed operation. Characteristically, FSM operates with a double electrical frequency and has attracted researchers' interest around the world [32-34].

Over the years, PMFSM has attracted attention due to its advantage of free-loss excitation. PMFSM has been designed in both inner and outer rotor configurations for various application. For automotive application, Fei *et al.* in [35] proposed three-phase Outer Rotor PMFSM (OR-PMFSM) for high torque density. It consists of C-stator core in which PMs in circumferential pattern are sandwiched between segment stator teeth. OR-PMFSM has benefit of high density but performance is affected by the use of C-core which reduces armature slot area [36]. In the same vein, the Outer Rotor HEFSM (OR-HEFSM) [37] in salient rotor has been proposed for high torque and power densities. It utilises two flux sources and requires external circuitry connection for excitation [37]. Consequently, OR-HEFSM has drawbacks of high iron loss and high winding loss, high flux leakage, poor temperature management and low armature reaction [38-39]. Furthermore, Outer Rotor FEFSM (OR-FEFSM) using segmented rotor in dovetail shape [40] has been proposed for high power density applications. OR-FEFSM replaced the PM in OR-PMFSM with field coil control capabilities. The use of rotor segment is to overcome high iron loss and weight associated with salient rotor regime [41]. OR-FEFSM has the advantage of low-cost

but requires an external DC source for excitation. It is obvious that both OR-HEFSM and OR-FEFSM require external DC source which increases winding loss and motor weight. Therefore, utilising the benefit of loss free excitation and reducing PM volume by 20 %, PMFSM would be discussed in this thesis. It is desirable to reduce iron loss in the salient rotor by replacing with segmented rotor in transverse shape and alternate tooth armature winding for high torque performance.

## 1.2 Problem statements

Outer rotor motors are becoming popular because they rotate slowly to overcome inertia and generate high torque for sustainable automotive applications [42]. Figure 1.1 depicts structures of outer rotor motors in segmented, salient and round rotors.




Figure 1.1: Cross-sections of three-phase outer rotor motors (a) OR-FEFSM (segmented rotor) [40] (b) OR-HEFSM (salient rotor) [37] (c) (d) SegStator-ORPMSM (round rotor) [21] OR-PMFSM (salient rotor) [35]



## REFERENCES

1. Villani, M. (2016). Induction machines, permanent magnet synchronous machines and others for cars and trucks – advantages and disadvantages of the types of machines. *7th International Conference on Magnetism and Metallurgy (WMM'14)*.
2. Jahns, T. (2017). Getting rare-earth magnets out of EV traction machines: a review of the many approaches being pursued to minimize or eliminate rare-earth magnets from future EV drivetrains. *IEEE Electrification Magazine*. 5(1). pp. 6-18.
3. Chiba, A. & Kiyota, K. (2015). Review of research and development of switched reluctance motor for hybrid electrical vehicle. *Proc. IEEE Workshop on Electrical Machines Design Control and Diagnosis*. pp. 127-131.
4. Jurkovic, S., Rahman, K. M., Morgante, J. C. & Savagian, P. J. (2015). Induction machine design and analysis for general motors e-assist electrification technology. *IEEE Transactions Industry Application*. 51(1). pp. 631-639.
5. Ribberink, H. & Evgueniy, E. (2013). Electric vehicles - a one-size-fits-all solution for emission reduction from transportation. *IEEE World Electric Vehicle Symposium and Exhibition (EVS27)*. pp. 1-7.
6. Jenal, M., Sulaiman, E. & Kumar, R. (2016). A new switched flux machine employing alternate circumferential and radial flux (ALCIRAF) permanent magnet for light-weight EV. *Journal of Magnetism*. 21(4). pp. 537-543.
7. Sulaiman, E., Kosaka, T. & Matsui, N. (2014). Design and analysis of high-power/high-torque density dual excitation switched-flux machine for traction drive in HEVs. *Renewable and Sustainable Energy Reviews*. 34. pp.517–524.
8. Shirani, M., Abbass, A., Saeed, S. & Jamali, J. (2015). A review on recent applications of brushless DC electric machines and their potential in energy saving. *Energy Equipment and Systems*. 3(1). pp. 57-71.

9. Widmer, J. D., Martin, R. & Kimiabeigi, M. (2015). Electric vehicle traction motors without rare earth magnets. *Sustainable Materials and Technologies, Elsevier*. 3. pp. 7-13.
10. Gnacinski, P. & Tarasiuk, T. (2016). Energy-efficient operation of induction motors and power quality standards. *Electric Power Systems Research*, 135, pp.10–17. doi: 10.1016/j.epsr.
11. Asım, G. Y., Mustafa, T., Barış, C., Ali İhsan, Ç. & Ayhan, G. (2018). Squirrel cage induction motor design and the effect of specific magnetic and electrical loading coefficient. *International Journal of Applied Mathematics Electronics and Computers*. 7(1). pp.1–8.
12. Márcio, R. C. R., Wanderson, R. H. A., Wesley, P. C. & Aylton, J. (2016). Analysis of switched reluctance motor efficiency under different speed control strategies. *CHILEAN Conference on Electrical, Electronics Engineering, Information and Communication Technologies*. pp. 468-472.
13. Zhang, G., Hua. W. & Cheng, M. (2016). Rediscovery of permanent magnet flux-switching machines applied in EV/HEVs: Summary of new topologies and control strategies. *Chinese Journal of Electrical Eng'g*. 2(2). pp.31-42.
14. Huynh, T., & Hsieh, M.F. (2018). Performance analysis of permanent magnet motors for electric vehicles (EV) traction considering driving cycles. *Energies*. 11(6). pp. 1-24.
15. Guo, Q., Zhang, C., Li, L., Gerada, D., Zhang, J. & Wang, M. (2017). Design and implementation of a loss optimisation control for electric vehicle in-wheel permanent-magnet synchronous motor direct drive system. *Applied Energy*. 204. pp. 1317–1332.
16. Yuan, W., Shao, P.W. & Shu, M.C. (2016). Choice of pole spacer materials for a high-speed PMSM based on the temperature rise and thermal stress. *IEEE Transactions on Applied Superconductivity*. 26(7). pp.1-5.
17. Gu, W., Zhu, X.Y., Li, Q. & Yi, D. (2015). Design and Optimisation of Permanent Magnet Brushless Machines for Electric Vehicle Applications. *Energies*. 8. pp. 13996–14008.
18. Buyukdegirmenci, V.T., Bazzi, A.M. & Krein, P.T. (2014). Evaluation of induction and permanent magnet synchronous machines using drive-cycle energy and loss minimization in traction applications. *IEEE Trans. Industry Applications*. 50(1). pp. 395-403.

19. Cheng, M., Sun, L., Buja, G. & Song, L. (2015). Advanced electrical machines and machine-based systems for electric and hybrid vehicles. *Energies*. 8(9). pp. 9541–9564.
20. Kim, Y. G., Bae, C. B., Kim, J. M. & Kim, H. C. (2010). Efficiency improvement by changeover of phase windings of multiphase permanent magnet synchronous motor with outer-rotor type. *25th Annual IEEE Applied Power Electronics Conference and Exposition (APEC)*. pp. 112-119.
21. Eclimo - EB25. (n.d.). Retrieved August 14, 2016, from <http://www.technologicvehicles.com/en/details/920/eclimo-eb25-prix-et-fiche-technique>.
22. Hwang, M. H., Han, J. H., Kim, D. H. & Cha, H.R. (2018). Design and analysis of rotor shapes for IPM motors in EV power traction platforms. *Energies*. 11(10). pp. 1-12.
23. Zhao, G. & Hua, W. (2017). A novel flux-switching permanent magnet machine with V-shaped magnets. *AIP Advances*. 7(5). pp. 0566551-0566555.
24. Khan, F., Erwan S. & Ahmad, M. Z. (2017). A novel wound field flux switching machine with salient pole rotor and non-overlapping windings. *Turkish Journal of Electrical Eng'rg & Computer Sciences*. 25. pp. 950 – 964.
25. Kosaka, T., Matsui, N., Kamada, T. & Kajiura, H. (2014). Experimental drive performance evaluation of high power density wound field flux switching motor for automotive applications. *7th IET International Conference on Power Electronics, Machines and Drives (PEMD)*. pp. 2-8.
26. Zhou, Y. J. & Zhu, Z. Q. (2014). Comparison of wound-field switched-flux machines. *IEEE Transactions on Industry Applications*. 50 (5). pp. 3314-3324.
- Sarlioglu, B. C., Morris, T., Han, D. & Li, S. (2017). Driving toward accessibility: A review of technological improvements for electric machines power electronics and batteries for electric and hybrid vehicles. *IEEE Ind. Appl. Mag.*, 23(1). pp. 14-25.
27. Zulu, A, Mecrow, B. C. & Armstrong, M. (2010). Topologies for wound-field three-phase segmented-rotor flux-switching machines. *5th IET International Conference on Power Electronics, Machines and Drives*. Brighton, UK. pp. 111-111.

28. Sulaiman, E., Kosaka, T. & Matsui, N. (2012). Design study and experimental analysis of wound field flux switching motor for HEV applications. *25th IEEE International Conference on Electrical Machines*. pp. 1269-1275.
29. Sanabria-Walter, C., Polinder, H., & Ferreira, J. A. (2013). High-torque-density high-efficiency flux-switching PM machine for aerospace applications. *IEEE Journal of Emerging and Selected Topics in Power Electronics*. 1(4). pp. 327-336.
30. Yilmaz, M. (2015). Limitations/capabilities of electric machine technologies and modelling approaches for electric motor design and analysis in plug-in electric vehicle applications. *Renewable and Sustainable Energy Reviews*. 52. pp, 80-99.
31. Taha, H. M. & Alnaab, I. (2019). Designs of PMSMs with inner and outer rotors for electric bicycle applications. *Kurdistan Journal of Applied Research*. 4(1). pp. 20-25.
32. Hua, W., Su, P., Tong, M. & Meng, J. (2016). Investigation of a five-phase E-core hybrid-excitation flux-switching machine for EV and HEV applications. *IEEE Transactions on Industry Applications*. 53(1). pp. 124-133.
33. Li, N., Lin, M., Yang, G., Kong, Y., Hao, L. & J. Zhu. (2018). A double stator axial field flux-switching memory machine with series permanent magnet and dc field winding. *IEEE International Conference on Applied Superconductivity and Electromagnetic Devices (ASEMD)*. pp. 1-2.
34. Hua, W., Zhang, H., Cheng, M., Meng, J. & Hou, C. (2017). An outer-rotor flux-switching permanent-magnet-machine with wedge-shaped magnets for in-wheel light traction. *IEEE Transactions on Industrial Electronics*. 64(1). pp. 69–80.
35. Fei, W., Luk, P.C.K., Shen, J. & Wang, Y. (2009). A novel outer-rotor permanent-magnet flux-switching machine for urban electric vehicle propulsion. *3rd International Conference on Power Electronics Systems and Applications*.
36. Ahmad, M. Z., Sulaiman, E., Haron, Z. A. & Kosaka, T. (2012). Preliminary studies on a new outer-rotor permanent magnet flux switching machine with hybrid excitation flux for direct drive EV applications. *IEEE International Conference on Power and Energy (PECon)*. pp. 928-933.

37. Xu, W., He, M. & Ye, C. (2016). Novel synchronous machine with permanent magnet in stator yoke. *IEEE Transactions on Applied Superconductivity*. 26(7). pp. 1-5.
38. Galea, M., Gerada, C. & Hamiti, T. (2012). Design considerations for an outer rotor, field wound, flux switching machine. *XXth International Conference on Electrical Machine*. pp. 171-176.
39. Yang, Y. & Shih, G. (2016). Optimal design of an axial-flux permanent-magnet motor for an electric vehicle based on driving scenarios. *Energies*. 9(4). pp. 1-18.
40. Xiang, Z., Quan, L. & Zhu, X. (2016). A new partitioned-rotor flux-switching permanent magnet motor with high torque density and improved magnet utilization. *IEEE Trans on Applied Superconductivity*. 26(4). pp. 1-5.
41. Li, G. J. & Zhu, Z. Q. (2016). Hybrid excitation switched flux permanent magnet machines with hybrid magnets. *8th IET International Conference on Power Electronics, Machines and Drives (PEMD)*. pp. 1-6.
42. Ahmad, N., Khan, F., Rashid A., Ayaz, K. & Sulaiman, E. (2018). Rotor pole study of outer rotor wound field flux switching motor for in wheel drive. *International Conference on Computing, Mathematics and Engineering Technologies (iCoMET)*. pp. 1-5.
43. Lee, C. H. T., Kirtley, J. L. & Angle, M. (2017). A partitioned-stator flux-switching permanent-magnet machine with mechanical flux adjusters for hybrid electric vehicles. *IEEE Transactions on Magnetics*. 53(11). pp. 1-7.
44. Suh, I. S., Hwang, K., Lee, M. & Kim, J. (2013). In-wheel motor application in a 4WD electric vehicle with foldable body concept. *International Electric Machines & Drives Conference*. pp. 1235-1240.
45. Ahmad, Z. M., Erwan, S. & Haron, Z. A. (2015). Optimal torque investigation of outer-rotor hybrid excitation flux switching machine for in-wheel drive EV. *ARPN Journal of Engineering and Applied Sciences*. 10 (19). pp. 8573-8580.
46. Noman, U., Faisal, K., Wasiq, U. & Abdul, B. (2018). Analytical modelling of open-circuit flux linkage, cogging torque and electromagnetic torque for design of switched flux permanent magnet machine. *Journal of Magnetics*. 23(2). 253-266.
47. Rauch, S. E & Johnson L. J. (1955). Design principles of flux-switch alternators. *AIEE Trans. Power Applications System*. 74(3). pp. 1261-1268.

48. Husin, Z. A., Sulaiman, E. & Kosaka, T. (2014). Design studies and effect of various rotor pole number of field excitation flux switching motor for hybrid electric vehicle applications. *IEEE 8th International Power Engineering and Optimisation Conference*. pp.114-119.
49. Yang, Y., Yang, X., Chen, P. & Wang, X. (2018). Electromagnetic performance analysis of hybrid excited segmental rotor flux switching machine. *IEEE Transactions on Magnetics*. 54(11). pp.1-5.
50. Awah, C. C. & Okoro, O. I. (2018). Coil and phase flux linkage characteristics of dual excited permanent magnet machines equipped with different winding configurations. *Nigerian Journal of Technology*. 37(3). pp. 758 – 769.
51. Owen, R., Zhu, Z. Q., Thomas, A., Jewell G. W. & Howe, D. (2010). Alternate pole wound flux switching permanent magnet brushless AC machines. *IEEE Transactions on Industry Applications*. 46(2). pp. 790-797.
52. Naderi, P., Sharouni, S. & Moradzadeh, M. (2019). Analysis of partitioned stator flux-switching permanent magnet machine by magnetic equivalent circuit. *International Journal of Electrical Power & Energy Systems*. 111. pp. 369-381.
53. Wang, L., Aleksandrov, S., Tang, Y., Paulides, J. J. H. & Lomonova, E. A. (2017). Fault-tolerant electric drive and space-phaser modulation of flux-switching permanent magnet machine for aerospace application. *IET Electric Power Applications*. 11(8). pp. 1416-1423.
54. Hao, L., Lin, M., Zhao, X. & Luo, H. (2011). Analysis and optimisation of EMF waveform of a novel axial field flux-switching permanent magnet machine. *Proceeding of International Conference on Electrical Machine System*. pp. 1-6.
55. Schao, Y., Nick, J., Baker, Mecrow, B. C., Hilton, C., Sooriyakumar, G., Perovic, D. K. & Fraser, A. (2014). Cost reduction of a permanent magnet in-wheel electric vehicle traction application. *IEEE International Conference on Electric Machines*. pp. 443-449.
56. Omar, M. F., Sulaiman, E., Khan, F., Romala, G. M. & Husin, Z. A. (2013). Comparison between single phase and three phase FEFSM with non-overlap windings and salient rotor. *ARNP Journal of Engineering and Applied Sciences*. pp. 1-5.



57. Pollock, C. & Wallace, M. (1999). The flux switching motor, a dc motor without magnets or brushes. *Proceeding of IEEE Industry Applications Society Annual Meeting (IAS)*. 3. pp. 1980–1987.
58. Pollock, C., Pollock, H., Barron, R., Coles, J. R., Moule, D., Court, A. & Sutton, R. (2006). Flux switching motors for automotive applications. *IEEE Transactions on Industry Applications*. 42 (5). pp. 1177-1184.
59. Sulaiman, E. & Kosaka, T. (2012). Parameter sensitivity study for optimisation of field-excitation flux switching synchronous machine for hybrid electric vehicles. *IEEE Conference on Industrial Electronics and Applications (ICIEA)*. pp. 52-57.
60. Dasgupta, A. K. (1960). Analytical method to find the best number of stator and rotor teeth of inductor alternator for 3-phase sinusoidal voltage generation. *AIEE Transactions on Power Applied Systems*. 79(50). pp. 674–679.
61. Bangura, J. F. (2006). Design of high-power density and relatively high efficiency flux-switching motor. *IEEE Trans. Energy Conversion*. 21(2). pp. 416-424.
62. Zhou, Y. J. & Zhu, Z. Q. (2013). Comparison of low-cost single phase wound-field switched-flux machines. *IEEE Trans. Ind. Appl.* 50(5). pp. 3335-3345.
63. Tang, Y., Paulides, J. J. H., Motoasca, T. E. & Lomonova, E. A. (2012). Flux-switching machine with DC excitation. *IEEE Transactions on Magnetics*. 48(11), pp. 3583-3586.
64. Khan, F., Sulaiman, E., Ahmad, M. Z. & Ali, H. (2014). Design refinement and performance analysis of 12slot-8pole wound field salient rotor switched-flux machine for hybrid electric vehicles. *12th IEEE International Conference on Frontiers of Information Technology*. pp. 197-201.
65. Sulaiman, E., Ali, H., Mubin, A. & Zhafir, A. (2015). Improved design of three phase hybrid excitation flux switching motor with segmental rotor. *Applied Mechanics and Materials*. 785. pp. 295-299.
66. Chen, J. T., Zhu, Z. Q. Iwasaki, S. & Deodhar, R. P. (2011). A novel hybrid-excited switched-flux brushless AC machine for EV/HEV applications. *IEEE Transactions on Vehicle Technology*. 60(4). pp. 1365–1373.
67. Othman, S.M.N.S. & Sulaiman, E. (2014). Design study of three-phase field excitation flux switching motor with outer rotor configuration. *IEEE Power Engineering Optimisation Conference*. pp. 230-234.

68. Zong, Z., Quan, L. & Xiang, Z. (2014). Comparison of double-stator flux-switching permanent magnet machine and double-stator permanent magnet synchronous machine for electric vehicle applications. *17th IEEE International Conference on Electrical Machines and Systems (ICEMS)*. pp. 234–239.
69. Kosaka, T., Matsui, N. & Sulaiman, E. (2011). A new structure of 12slot-10pole field-excitation flux switching synchronous machine for hybrid electric vehicles. *European Conference on Power Electronics and Applications (EPE)*. pp. 1-10.
70. Lian, G., Gu, G., Cheng, Y., Tao, J., Wang, S. & Chen, X. (2015). Comparative study on switched reluctance and flux-switching machines with segmental rotors. *18th IEEE International Conference on Electrical Machines and Systems (ICEMS)*. pp. 845-848.
71. Hoang, E., Lecrivain, M. & Gabsi, M. (2007). A new structure of a switching flux synchronous polyphased machine with hybrid excitation. In *Proc. Eur. Conference on Power Electronic Applications*. pp. 1–8.
72. Sangdehi, S. K., Abdollahi, S. E. & Gholamian, S. A. (2017). A segmented rotor hybrid excited flux switching machine for electric vehicle application. *8th Power Electronics, Drive Systems & Technologies Conference (PEDSTC)*. pp. 347-352.
73. Amara, Y., Vido, L., Gabsi, M., Hoang, E., Lecrivain, M. & Chabot, F. (2006). Hybrid excitation synchronous machines: energy efficient solution for vehicle propulsion. *IEEE Vehicle Power Propulsion Conference*. 58(5). pp. 1–6.
74. Hoang, E., Hlioui, S., Lecrivain, M. & Gabsi, M. (2009). Experimental comparison of lamination material case switching flux synchronous machine with hybrid excitation. *Proc. of European Conference on Power Electron Application*. pp. 1-7.
75. Jafar, N. A. & Sulaiman, E. (2014). Design analysis of 12S-10P hybrid-excitation flux-switching permanent-magnet machines for hybrid electric vehicle. *Proc. IEEE 8th International Power Eng. Optimisation Conference*. 4. pp. 308–312.
76. Nakane, H. Kosaka, T. & Matsui, N. (2015). Design studies on hybrid excitation flux switching motor with high power and torque densities for HEV applications. *IEEE International Electric Machines & Drives Conference (IEMDC)*. pp. 234-239.



77. Maeda, Y., Kosaka, T. & Matsui, N. (2016). Design study on hybrid excitation flux switching motor with permanent magnet placed at middle of field coil slot for HEV drives. *XXII International Conference on Electrical Machines (ICEM)*. pp. 2522-2528.
78. Sulaiman, E., Khan, F. & Kosaka, T. (2016). Field-excited flux switching motor design, optimisation and analysis for future hybrid electric vehicle using finite element analysis. *Progress in Electromagnetics Research B*. 71. pp.153–166. doi:10.2528/pierb16092502.
79. Liao, Y., Liang, F. & Lipo, T. A. (1992). A novel permanent magnet motor with doubly salient structure. *Proc. Conf. Rec. IEEE IAS Annual Meeting*. pp. 308-314.
80. Zhu, Z.Q. (2011). Switched flux permanent magnet machines: Innovation continues. *Proc. Int. Conf. on Electrical Mach. Systems (ICEMS)*. pp. 1-10.
81. Hua, W., Cheng, M. & Zhang, G. (2009). A novel hybrid excitation flux-switching motor for hybrid vehicles. *IEEE Trans. Magnetics*. 45(10). pp. 4728-4731.
82. Andre, N., Sami, H., Mohamed, G., Mathieu, M. & Didier, L. (2017). Experimental investigation of a doubly-excited flux-switching machine for aircraft dc power generation *IEEE International Electric Machines & Drives Conference*. pp. 1-8.
83. Tuncay, R. N., Ustun, O., Yilmaz, M., Gokce, C. & Karakaya, U. (2011). Design and implementation of an electric drive system for in-wheel motor electric vehicle applications. *IEEE Vehicle Power and Propulsion Conference*. pp. 1-6.
84. Erwan, S. *Design studies on less rare-earth and high power density flux switching motors with hybrid excitation/wound field excitation for HEV drives*. Ph.D thesis. Nagoya Institute of Technology Nagoya Japan; 2012.
85. Arvind, K., & Ajay, S. (2016). Performance investigation of various flux switching machines for hybrid electric vehicles: A review. *International Journal of Research in Electrical, Electronic and Instrumentation Engineering*. 5(12). pp. 9246-9256.
86. Deodhar, R. P., Andersson, S., Boldea, I. & Miller, T. J. (1997). The flux-reversal machine: A new brushless doubly-salient permanent-magnet machine. *IEEE Transactions on Industry Applications*. 33(4). pp. 925-934.

87. Souma, K., Tanigawa, S., Moue, I., Kikuchi, H. & Iwasaki, T. (2015). High-performance materials for electric drive solutions. *Hitachi Review*, 60(1). 55.
88. Yao, Y., Liu, C. & Lee, C. H. T. (2018). Quantitative comparisons of six-phase outer-rotor permanent-magnet brushless machines for electric vehicles. *Energies*. 11(8). pp. 1-18.
89. Gaussens, B., Hoang, E., Lecrivain, M., Manfe, P. & Gabsi, M. (2014). Hybrid-excited flux-switching machine for high speed DC-alternator applications. *IEEE Transactions on Industrial Electronics*. 61(6). pp. 2976-2989.
90. Kong, Y., Lin, M., Xu, D., Li, N., Fu, X. & Liu, K. (2017). Design and analysis of outer-rotor permanent magnet synchronous machine with amorphous stator core. *20th IEEE International Conference on Electrical Machines and Systems (ICEMS)*. pp. 1-5.
91. Fei, W., Luk, P. C. K., Bing, X. & Demin, W. (2013). Design improvement of outer-rotor permanent magnet flux switching machine for direct-drive urban electric vehicle propulsion. *39th Annual Conference of the IEEE Industrial Electronics Society*. pp. 7319-7324.
92. Jusoh, L. I., Erwan, S., Kumar, R., Bahrim, F. S. & Omar, M. F. (2017). Preliminary studies of various rotor pole number for permanent magnet flux switching machines. *International Journal of Applied Engineering Research*. 12 (7). pp. 1377-1382.
93. Syed, Q. A. S., Kurtović, H. & Hahn, I. (2017). New single-phase flux switching axial flux permanent magnet motor. *IEEE Transactions on Magnetics*. 53(11). pp. 1-5.
94. Hoang, E., Ben-Ahmed, A. H. & Lucidarme, J. (1997). Switching flux permanent magnet poly-phased synchronous machines. *Proceeding of 7th European Conference on Power Electronics and Applications (EPE)*. 3. pp. 903–908.
95. Ur Rahman, L., Khan, F., Khan, M. A., Ahmad, N., Khan, H. A. & Shahzad, M. (2019). Modular rotor single phase field excited flux switching machine with non-overlapped windings. *Energies*. 12(8). pp. 1-27.
96. Chen, J. T., Zhu, Z. Q., Iwasaki, S. & Deodhar, R. (2010). A novel E-core flux switching PM brushless AC machine. *Proceeding of IEEE Energy Conversion Congress and Exposition*. pp. 3811–3818.

97. Xu, W., Lei, G., Wang, T., Yu, X., Zhu, J. & Guo, Y. (2012). Theoretical research on new laminated structure flux switching permanent magnet machine for novel topologic plug-in hybrid electrical vehicle. *IEEE Transactions on Magnetics*. 48(11). pp. 4050-4053.
98. Li, F., Hua, W., Tong, M., Zhao, G. & Cheng, M. (2015). Nine-phase flux-switching permanent magnet brushless. *IEEE Trans. Magn.* 51(3). pp. 34–37.
99. Senthil, A, Kumar, Prasath Vijay Raj T, and Tharagesh V. Prasanna. (2018). Design and analysis of a permanent magnet DC motor. in Konkani, A., Bera, R. & Paul, S. *Advances in Systems, Control and Automation*. Springer. pp. 237-249.
100. Fei, W., Luk, P. C. K. & Shen, J. (2011). Design and analysis of a new outer-rotor permanent-magnet flux-switching machine for electric vehicle. *The International Journal for Computation and Mathematics in Electrical and Electronic Engineering*. 30(1). pp. 48-61.
101. Zhu, Z. Q., & Chen, J. T. (2010). Advanced flux-switching permanent magnet brushless machines. *IEEE Transactions on Magnetics*. 46 (6). pp. 1447-1453.
102. Cai, J., Lu, Q. Jin., Y., Chen, C. & Ye, Y. (2011). Performance investigation of multi-tooth flux- switching PM linear motor. *International Conference on Electrical Machines and Systems (ICEMS)*. pp. 1 – 6.
103. Xiaohe, M., Yang, Y., Rong, S., Jet, T. K., Vaiyapuri, V., Amit, G. & Chandana, G. (2016). Comparative analysis of flux switching machines between toothed rotor with permanent magnet excitation and segmented rotor with field coil excitation. *IECON Annual Conference of the IEEE Industrial Electronics Society*. pp. 1610-1615.
104. Zhu, Z. Q., Pang, Y., Chen, J. T., Owen, R. L., Howe, D., Iwasaki, S. Deodhar, R. & Pride, A. (2008). Analysis and reduction of magnet eddy current loss in flux-switching permanent magnet machines. *Proc. 4th IET Conference Power Electron*. pp. 120-124.
105. Raminosoa, T., & Gerada, C. (2010). Fault tolerant winding technology comparison for flux switching machine. *XIX IEEE International Conference on Electrical Machines (ICEM)*. pp. 1-6.
106. Li, S.L., Li, Y. J. & Sarlioglu, B. (2015). Performance assessment of high-speed flux switching permanent magnet machine using ferrite and rare earth

- permanent magnet materials. *Electric Power Components and Systems*. pp. 711–720.
107. Thomas, A., Zhu, Z. Q., Jewell, G. W. & Howe, D. (2008). Flux-switching PM brushless machines with alternative stator and rotor pole combinations. *IEEE International Conference on Electrical Machines and Systems*. pp. 2986-2991.
  108. Chin, Y. K. & Soulard, J. (2003). A permanent magnet synchronous motor for traction applications of electric vehicles. *IEEE International Electric Machines and Drives Conference*. pp.1035-1041.
  109. Zulu, A., Mecrow, B. C. & Armstrong, M. (2012). Permanent magnet flux switching synchronous motor employing a segmental rotor. *IEEE Transactions on Industries*. 6. pp. 2259-2267.
  110. Thomas, A. S., Zhu, Z. Q. & Wu, L. J. (2012). Novel modular- rotor switched flux permanent magnet machines. *IEEE Transactions on Industry Applications*. 48(6). pp. 2249-2258.
  111. Kumar, R.H. *Refinement of outer rotor permanent magnet flux switching machine for downhole application*. Master's thesis. Universiti Tun Hussein Onn Malaysia; 2017.
  112. Aravind, C.V. (2013). *Design and development of double-rotor switched reluctance motor using magnetic circuit analysis*. Ph.D thesis. Universiti Putra Malaysia; 2013.
  113. Fei, W. Z. & Shen, J. X. (2006). Comparative study and optimal design of PM switching flux motors. *Proceedings of the 41st International Universities Power Engineering Conference*. 2. pp. 695-699.
  114. Jia, H., Cheng, M., Hua, W., Lu, W. & Fu, X. (2008). Investigation and implementation of control strategies for flux-switching permanent magnet motor drives. In *IEEE Industry Applications Society Annual Meeting*. pp. 1-6.
  115. Kabir, M. A. & Iqbal, H. (2015). Concentrated winding segmented rotor switched reluctance machine (SRM) using three-phase standard inverters. *IEEE Energy Conversion Congress and Exposition (ECCE)*. pp. 5567-5572.
  116. Pang, Y., Zhu, Z. Q., Howe, D., Iwasaki, S., Deodhar, R. & Pride, A. (2006). Eddy current loss in the frame of a flux-switching permanent magnet machine. *IEEE Transactions on Magnetics*. 42(10). pp. 3413-3415.

117. Ilhan, E., Kremers, M. F. J., Motoasca, E. T., Paulides, J. J. H. & Lomonova, E. A. (2012). Sensitivity analysis for phase inductances in flux-switching PM machines. *Proc. Int. Conference on Electrical Machines*. pp.763-768.
118. Zhu, Z. Q. & Evans, D. (2015). Overview of recent advances in innovative electrical machines - with particular reference to magnetically geared switched flux machines. *17th International Conference on Electrical Machines and Systems, (ICEMS)*.
119. Xiaohe, M., Rong, S., Jet, T. K., Shuai, W., Xiaolong, Z., Vaiyapuri, V. & Sivakumar, N. (2015). Review of high speed electrical machines in gas turbine electrical power generation. In *IEEE TENCON Conf. Region 10*. pp. 1-9.
120. Risticvic, M. Iles D., Moeckel, A. & Gmbh, R. B. (2016). Design of an interior permanent magnet synchronous motor supported by the topology optimisation algorithm. *International Symposium on Power Electronics, Electrical Drives, Automation and Motion*. pp. 221–225.
121. Dyck, D. N. & Lowther, D. A. (1996). Automated design of magnetic devices by optimising material distribution. *IEEE Transactions on Magnetics*. 32(3). pp. 1188–1192.
122. Byun, J. & Hahn, S. (1999). Topology optimisation of electrical devices using mutual energy and sensitivity. *IEEE Transactions on Magnetics*. 35(5). pp. 3718–3720.
123. Chang-Hwan, I., Jung, H. & Kim, Y. (2003). Hybrid genetic algorithm for electromagnetic topology optimisation. *IEEE Transactions on Magnetics*. 39(5). pp. 2163–2169.
124. Wang, Y., Jin, M. J., Z. Fei, W. Z. & Shen, J. X. (2010). Cogging torque reduction in permanent magnet flux-switching machines by rotor teeth axial pairing. *IET Electric Power Application*. 4(7). pp. 500–506.
125. Iles-klumpner, D., Risticvic, M. & Boldea, I. (2005). Advanced optimisation design techniques for automotive interior permanent magnet synchronous machines. *IEEE International Conference on Electric Machines and Drives*. pp. 227–234.
126. Kim, D. H., Sykulski, J. K. & Lowther, D. A. (2009). The implications of the use of composite materials in electromagnetic device topology and shape optimisation. *IEEE Transactions on Magnetics*. 45(3). pp. 1154–1157.

127. Sulaiman, E., Kosaka, T. & Matsui, N. (2011). Parameter optimisation study and performance analysis of 6S-8P permanent magnet flux switching machine with field excitation for high speed hybrid electric vehicles. *Proceedings of the 14th European Conference on Power Electronics and Appliance*. pp. 1-9.
128. Choi, J. S. & Yoo, J. (2009). Structural topology optimisation of magnetic actuators using genetic algorithms and ON/OFF sensitivity. *IEEE Transactions on Magnetics*. 45(5). pp. 2276–2279.
129. Zulu, A. *Flux switching machines using segmental rotors*. Ph.D thesis. Newcastle University; 2010.
130. Fei, W. Z. & Shen, J. X. (2006). Comparative study and optimal design of PM switching flux motors. *Proceedings of the 41st International Universities Power Engineering Conference*. 2. pp. 695-699.
131. Nagoor Kani, A. A Simplified Text in Electrical Machine Design. In: *Electric Machinery*. Chennai: RBA Publications. 1: pp. 7-35; 2012.
132. Zhu, L., Jiang, S., Zhu, Z.Q. & Chan, C. (2009). Analytical methods for minimizing cogging torque in permanent magnet machines. *IEEE Transactions on Magnetics*. 45(4). pp. 2023-2031.
133. Ahmad M. Z. *Design and optimisation of outer rotor hybrid excitation flux switching motor*. Ph.D thesis. Universiti Tun Hussein Onn Malaysia; 2016.
134. Chukwuma, J. I. *A high torque density, direct-drive in-wheel motor for electric vehicle*. Ph.D thesis. Newcastle University; 2013.
135. Gulec, M., Yolacan, E., Demir, Y., Ocak, O. & Aydin, M. (2016). Modelling based on 3D finite element analysis and experimental study of a 24-slot 8-pole axial flux permanent-magnet synchronous motor for no cogging torque and sinusoidal back-EMF. *Turkish Journal of Electrical Engineering and Computer Science*. 24. pp. 262–275.
136. Liang, X. & Luy, Y. (2006). Harmonic analysis for induction motors. *Canadian Conference on Electrical and Computer Engineering*. pp. 172-177. doi: 10.1109/CCECE.2006.277368.



### LIST OF PUBLICATIONS AND AWARDS

Following is the list of publications in the result of research presented in this thesis.

#### *Journals*

- [1] Enwelum I Mbadiwe; Erwan Sulaiman "Flux Switching Permanent Magnet Motor using Segmented Outer Rotor Structure for Electric Scooter" Indonesian Journal of Electrical Engineering and Computer Science, Vol. 6, No. 2, May 2017, pp. 379 ~ 386 DOI: 10.11591/ijeecs.v6.i2. pp379-386. (Scopus indexed)
- [2] Enwelum I Mbadiwe; Erwan Sulaiman; Ahmad Md Zafari; Siti Khalidah Rahimi, "High Torque Flux Switching Permanent Magnet Machine in Segmented Outer Rotor using Appropriate Split Ratio for Electric Scooter Propulsion" International Journal on Power Electronics and Drives Systems (IJEPPDS) Vol 8, No 4: December 2017. (Scopus indexed)
- [3] Enwelum I. Mbadiwe and Erwan Sulaiman, "Evaluation of Performance of Flux Switching Motor in Segmented Rotor Using Permanent Magnet for Direct Drive," International Journal of Engineering and Technology, [www.sciencepubco.com/index.php/ijet/article/view/22328](http://www.sciencepubco.com/index.php/ijet/article/view/22328). (Scopus indexed)
- [4] Enwelum I. Mbadiwe, Erwan B. Sulaiman, Ahmad Md. Zafari, "Torque Performance Analysis of Three-Phase Permanent Magnet Flux Switching Motor in Out-runner Segmented Rotor for In-Wheel High Torque Vehicles," International Journal of Electrical and Electronic Engineering & Telecommunications, Vol. 8, No. 1, pp. 14-18, January 2019. Doi: 10.18178/ijeetc.8.1.14-18. (Scopus indexed)
- [5] Enwelum I. Mbadiwe and Erwan Sulaiman, "Permanent Magnet Switched Flux Motor Torque Capability: A Reliable Solution to Fuelless Vehicle Application", International Journal of Renewable Energy Resources, 7(1), 8-14, 2018. (Scopus indexed)
- [6] Enwelum I. Mbadiwe, Erwan B. Sulaiman, Liew Chung Peng. "Sustainable High Torque for Electric Scooter Propulsion Using Permanent Magnet Flux Switching Machine Technology," Journal of Engineering Science and

Technology Special Issue on SU18, February (2019) 286 – 299. (Scopus indexed)

### *Proceeding*

- [7] Enwelum I Mbadiwe; Erwan Sulaiman; Ahmad Md Zarafi, "A High Torque Segmented Outer Rotor Permanent Magnet Flux Switching Motor for Motorcycle Propulsion" Malaysian Technical Universities Conference on Engineering and Technology, December 2017, in MATEC Web of Conferences.
- [8] Enwelum I. Mbadiwe and Erwan Sulaiman "Improved Design of Outer Rotor Machine in PM Technology for Motor-Bike Drive Application" 2018 IEEE Symposium on Computer Applications & Industrial Electronics (ISCAIE) IEEE Xplore: 09 July 2018. (Scopus indexed)
- [9] EI Mbadiwe, E Sulaiman, F Khan "Consideration of permanent magnet flux switching motor in segmented rotor for in-wheel vehicle propulsion, International Conference on Computing, Mathematics and Engineering Technologies, 2018 - ieeexplore.ieee.org. (Scopus indexed).
- [10] Enwelum I. Mbadiwe and Erwan Sulaiman. "Sustainable Electric Machine Torque Performance using Segmented Rotor and PM Technology for Direct Drive Vehicle Application," 2019 IEEE International Conference on Automatic Control and Intelligent Systems (I<sup>2</sup>CACIS), Selangor, Malaysia, 2019, pp. 118-122. (Scopus indexed).
- [11] Enwelum I. Mbadiwe, L. Iwani Jusoh, S. M. Naufal and E. Sulaiman, "High Performance Flux Switching Machine using Segmented Rotor and PM Technology for In-Wheel Motorcycle and Scooter Applications," 2019 IEEE 15th International Colloquium on Signal Processing & Its Applications (CSPA), Penang, Malaysia, 2019, pp. 168-173. (Scopus indexed).
- [12] Enwelum I. Mbadiwe, Syed Muhammad Naufal bin Syed Othman, Erwan bin Sulaiman. Comparative Study of PM Flux Switching and Surface Mounted PM Synchronous Machines for Direct-drive Vehicle Applications. 2019 IEEE 10th Control and System Graduate Research Colloquium (ICSGRC), Shah Alam, Malaysia, 2019, pp. 41-45. doi: 10.1109/ICSGRC.2019.8837057.



- [13] Enwelum I. Mbadiwe and Erwan Sulaiman, A review of various structures and performances of flux switching machine in salient and segmented rotors using PM for EV applications, IEEE Access. ISI Technical Paper, *Under review*
- [14] Erwan Sulaiman and Enwelum I. Mbadiwe, Design and Optimization of Outer-Rotor Permanent Magnet Flux Switching Motor using Transverse Segmental Rotor for Automotive Applications, IETPA Electric Power Applications. Research paper *Under Review*. (ISI)

### Awards

Silver Medal ITEX KLCC May 2016.

Exhibition & Seminars Product Showcase, Exhibition, Innovation, Invention, UTHM RISE 2018, Nov 13-14/2018 "BRONZE MEDAL"

Best Paper Presenter in 2019 CSPA at Penang, Malaysia on March 8/2019.

RISE 2019, September GOLD MEDAL and PRIZE.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH